# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No: MEDB000040T

Revision No:

2

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV GL SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

## This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: floor coverings

with type designation(s) Sikafloor® Marine 609 with Color Flake

# Issued to Sika Services AG Zürich, ZH, Switzerland

is found to comply with the requirements in the following Regulations/Standards: Regulation (EU) 2019/1397, item No. MED/3.18c. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2024-05-19**. Issued at **Hamburg** on **2020-01-09** 

DNV GL local station: **Augsburg** 

Approval Engineer: Roland Priebe



Notified Body No.: 0098 for DNV GL SE

Gerhard Aulbert Head of Notified Body

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Page 1 of 2

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment", signed February 27th, 2004, and amended by Decision No 1/2018 dated February 18th, 2019.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being

 Job Id:
 344.1-008097-3

 Certificate No:
 MEDB000040T

 Revision No:
 2

# Product description

Sikafloor® Marine 609 with color flakes is an epoxy resin consisting of two components.

Max. applied thickness: 0.2 mm Density : 1,1 Kg/m<sup>3</sup> Maximum organic content: 100% Approved colour: transparent

For further details refer to the documentation listed below under "Type Examination documentation".

# **Application/Limitation**

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as floor covering on any low flame-spread floor covering, steel or non-combustible material.

Several layers of floor coverings are acceptable provided that each layer is approved according to the Marine Equipment Directive and bear the mark of Conformity.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Each product is to be supplied with its manual for installation, use and maintenance.

#### **Type Examination documentation**

Test report No. 8P01619rev1 dated 17<sup>th</sup> Mai 2019 from RISE Research Institute of Sweden AB, Boras, Sweden.

## **Tests carried out**

Tested according to IMO 2010 FTP Code Annex 1, Part 2 and Part 5.

#### Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, fire technical rating, Mark of Conformity and USCG approval number (see first page).