

BUILDING TRUST

PRODUCT DATA SHEET Sika[®] Cleaner PCA

Cleaning pad and primer applicator

TYPICAL PRODUCT DATA

Chemical base	Open pors, expanded melamine resin
Color (CQP001-1)	Light grey
	Dry scrub or wet scrub with Sika [®] CleanGlass or Sika [®] Cleaner G+P

DESCRIPTION

Sika[®] Cleaner PCA is a smart cleaning pad based on melamine foam. It is used for removal of contamination or cleaning of windshields and other surfaces.

Additionally it can be used to apply certain $\mathsf{Sika}^{\texttt{0}}$ Primers.

PRODUCT BENEFITS

- Quick, clean and simple way to remove contamination and label residues.
- Suitable as primer applicator
- EHS friendly

AREAS OF APPLICATION

Sika[®] Cleaner PCA is designed for the removal of contamination on ceramic frits or glass. It can also be used for the removal of label residues and other kinds of contamination. Sika[®] Cleaner PCA is well suited to apply Sika[®] Primers used in the Automotive Glass Replacement business.

This product is suitable for experienced professional users only. Tests with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

METHOD OF APPLICATION

To remove the contamination from windshields, use Sika[®] CleanGlass respectively Sika[®] Cleaner G+P or an equivalent non antistatic glass cleaner to wet the surface and detect contamination. Start scrubbing with a Sika[®] Cleaner PCA the bond area. For heavy contamination Sika[®] Cleaner PCA can be used dry to increase effectivness.

Always consider that it is designed for single use application only.

Wipe the Sika[®] CleanGlass off and allow the surface to dry completely before the next step in surface preparation is performed.

IMPORTANT NOTE

Compatibility with the current substrate has to be verified prior to the application. Before using Sika® Cleaner PCA to sensitive surfaces (e.g. plastics, etc.) it is recommended to test it on a small, possibly non-visible area of the base material.

Prior the adhesive application the surface has to be pre-treated according to Sika's surface preparation recommendations.

FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

Copies of the following publications are available on request:

Safety Data Sheets

PACKAGING INFORMATION

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

DISCLAIMER

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PRODUCT DATA SHEET Sika® Cleaner PCA Version 01.01 (02 - 2022), en_KE 019400000030020000 Sika Kenya Limited Semco Industrial Park 2nd/ Floor, Mombasa Road P.O Box 38645 - 00623 Nairobi, Kenya Mobile: +254 711 140234 Web: Ken.sika.com

